

VICTRONIX	Add:	Room 1405A, Building 1B, Hua qiang Idea Park, Guang Ming District, ShenZhen,China		
	Tel:	+86-755-33265935	Fax:	+86-755-33265935

SPECIFICATION

VXT10QIH-07C

☐ Preliminary Specification

☐ Final Specification



CUSTOMER:

Made By:

Checked By:

Approved By:

Quality:

Date:

Note:

Approved By:

Date:

Note:

[illegible]

3. General Specifications

VXT101QIH-07C is a TFT-LCD module. It is composed of a TFT-LCD panel, driver IC, FPC, CTP, a back light unit. The 10.1" display area contains 1280X800 pixels and can display up to 16.7M colors. This product accords with RoHS

Item	Contents	Unit	Note
LCD Type	TFT	-	
Display color	16.7M		1
Viewing Direction	Free view	O'Clock	
Operating temperature	-20---+70	°C	
Storage temperature	-30---+80	°C	
Module size	Refer to outline drawing	mm	2
Active Area(W×H)	216.96X135.6	mm	
Number of Dots	1280×800	dots	
Controller for LCD	--	-	
Driver for CTP	GT928		
Power Supply Voltage	5.0	V	
Outline Dimensions	Refer to outline drawing	-	
Backlight	3X10-LEDs (white)	pcs	
Weight	---	g	
Interface	LVDS	-	

The technical drawing illustrates the VXT101QH-07C module from three perspectives: top, front, and back. The top view shows a rectangular module with a central display area of 101.1 TFT (1280(RGB)X800). Dimensions include a total width of 245.5 CTP and a height of 163.6 CTP. The front view shows the module's profile with a 1.1 LENS and a 2.5 BL. The back view shows the connector and PET layers. A detailed LED circuit diagram shows a 3x10=30 LED array with pins A and K. A table of CTP (Center to Pin) assignments is provided, listing pins 1 through 40 and their corresponding functions. The drawing also includes a title block with the module name, drawing number, and company information.

PIN	FUNCTION
1	VDD
2	VDD
3	VDD
4	NC
5	NC
6	NC
7	GND
8	Rxin0-
9	Rxin0+
10	GND
11	Rxin1-
12	Rxin1+
13	GND
14	Rxin2-
15	Rxin2+
16	GND
17	RxCCLK-
18	RxCCLK+
19	GND
20	Rxin3-
21	Rxin3+
22	GND
23	NC
24	NC
25	GND
26	NC
27	LED_PWM
28	NC
29	AVDD
30	GND
31	LED-
32	LED-
33	NC
34	WAKE
35	VGL
36	NC
37	CABC_EN
38	VGH
39	LED+
40	LED+

5. Absolute Maximum Ratings(Ta=25°C)

5.1 Electrical Absolute Maximum Ratings.(Vss=0V ,Ta=25°C)

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	V _{DD}	-0.3	6.0	V	1, 2

Notes:

1. If the module is above these absolute maximum ratings. It may become permanently damaged.

Using the module within the following electrical characteristic conditions are also exceeded, the module will malfunction and cause poor reliability.

2. V_{DD} > V_{SS} must be maintained.

5.2 Environmental Absolute Maximum Ratings.

Item	Storage		Operating		Note
	MIN.	MAX.	MIN.	MAX.	
Ambient Temperature	-20°C	60°C	0°C	50°C	1,2
Humidity	-	-	-	-	3

1. The response time will become lower when operated at low temperature.

2. Background color changes slightly depending on ambient temperature.

The phenomenon is reversible.

3. Ta<=40°C:85%RH MAX.

Ta>=40°C:Absolute humidity must be lower than the humidity of 85%RH at 40°C.

6. Electrical Specifications and Instruction Code

6.1 Electrical characteristics(V_{ss}=0V ,T_a=25°C)


Parameter	Symbol	Min	Typ	Max	Unit	Note
Power supply	VDD	2.3	2.5	2.7	V	
	AVDD	8.0	8.2	8.4	V	
	VGH	21.7	22	22.3	V	
	VGL	-7.3	-7	-6.7	V	
Input singal voltage	VCOM	3.0	3.3	3.6	V	
Input logic high voltage	VIH	0.8VDD		VDD	V	
Input logic low voltage	VIL	0		0.2VDD	V	
Clock frequency	1/TC		71		MHZ	

Note:

1: Tested in 1×1 chessboard pattern.

6.2 LED backlight specification(VSS=0V ,Ta=25°C)

Item	Symbol	Condition	Min	Typ	Max	Unit	Note
Supply voltage	Vf	If=20X10mA	-	9.0	-	V	
Uniformity	Δ Bp	If=20X10mA	70			%	
Luminance for LCD (W/O CTP)	Lv	If=20X10mA	-	250		Cd/m2	



I_{LED} VS TEMP

6.3 Interface signals （Connector: F62240-H1210A）

Pin No.	Symbol	I/O	Function
1	VCOM	P	COMMON voltage
2~3	VDD	P	Power supply.
4~6	NC		No connection.
7	GND	P	Ground.
8	Rxin0-	I	-LVDS differential data input
9	Rxin0+	I	+LVDS differential data input
10	GND	P	Ground.
11	Rxin1-	I	-LVDS differential data input
12	Rxin1+	I	+LVDS differential data input
13	GND	P	Ground.
14	Rxin2-	I	-LVDS differential data input
15	Rxin2+	I	+LVDS differential data input
16	GND	P	Ground.
17	RxCLK-	I	-LVDS differential data input
18	RxCLK+	I	+LVDS differential data input
19	GND	P	Ground.
20	Rxin3-	I	-LVDS differential data input
21	Rxin3+	I	+LVDS differential data input
22	GND	P	Ground.
23~24	NC		No connection.
25	GND	P	Ground.
26	NC		No connection.
27	LED_PWM	I	CABC controller signal output for backlight
28	NC		No connection.
29	AVDD	P	Power for analog circuit.
30	GND	P	Ground.
31~32	LED-	P	LED cathode
33~34	NC		No connection.
35	VGL	P	Gate off voltage
36	NC		No connection.
37	CABC_EN	I	CABC enable input.
38	VGH	P	Gate on voltage
39~40	LED+	P	LED anode.

Pin	Enable	Disable
CABC_EN	High Voltage	Low Voltage or open

CTP interface

Pin No	Symbol	I/O	Function
1	VDD-3.3V	P	CTP Power supply
2	WAKE		
3	INT	p	External Interrupt to the IC of CTP
4	SCL	I	Serial clock
5	SDA	I	Serial Input/output data bus
6	GND	P	Ground

7. Optical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Brightness (With CTP)	Bp	$\theta=0^\circ$ $\Phi=0^\circ$	-	250	-	Cd/m ²	1
Uniformity	ΔBp		70	-	-	%	1,2
Viewing Angle	3:00	Cr $\geq$ 10	-	80	-	Deg	3
	6:00		-	80	-		
	9:00		-	80	-		
	12:00		-	80	-		
Contrast Ratio	Cr	$\theta=0^\circ$ $\Phi=0^\circ$	300	500		-	4
Response Time	T _r		-	10	-	ms	5
	T _f		-	15	-	ms	
Color of CIE Coordinate	W	x		0.28		-	1,6
		y		0.33		-	
	R	x		0.51		-	
		y		0.34		-	
	G	x		0.31		-	
		y		0.56		-	
	B	x		0.15		-	
		y		0.14		-	


Note: The parameter is slightly changed by temperature, driving voltage and material

Note 1: The data are measured after LEDs are turned on for 5 minutes. LCM displays full white.
The brightness is the average value of 9 measured spots. Measurement equipment
PR-705 (Φ8mm)

Measuring condition:

- Measuring surroundings: Dark room.
- Measuring temperature: Ta=25°C.
- Adjust operating voltage to get optimum contrast at the center of the display.

Measured value at the center point of LCD panel after more than 5 minutes while
backlight turning on.




Note 2: The luminance uniformity is calculated by using following formula.

$$\Delta Bp = Bp (\text{Min.}) / Bp (\text{Max.}) \times 100 (\%)$$


$Bp (\text{Max.})$ = Maximum brightness in 9 measured spots

$Bp (\text{Min.})$ = Minimum brightness in 9 measured spots.




Note 3: The definition of viewing angle:

Refer to the graph below marked by θ and ϕ




Note 4: Definition of contrast ratio.(Test LCD using DMS501)



$$\text{Contrast ratio}(Cr) = \frac{\text{Brightness of selected dots}}{\text{Brightness of non-selected dots}}$$


Note 5: Definition of Response time. (Test LCD using DMS501):

The output signals of photo detector are measured when the input signals are changed from “black” to “white”(falling time) and from “white” to “black”(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figure as below.



The definition of response time

Note 6: Definition of Color of CIE Coordinate and NTSC Ratio.




Color gamut:

$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$

Note 7: Definition of cross talk.

$$\text{Cross talk ratio(\%)} = \frac{|\text{pattern A Brightness} - \text{pattern B Brightness}|}{\text{pattern A Brightness}} \times 100$$



Electric volume value=3F+/-3Hex

8. Reliability Test Items and Criteria

No	Test Item	Test condition	Criterion
1	High Temperature Storage	60°C 96H Restore 2H at 25°C Power off	1. After testing, cosmetic and electrical defects should not happen. 2. Total current consumption should not be more than twice of initial value.
2	Low Temperature Storage	-20°C±2°C 96H Restore 2H at 25°C Power off	
3	High Temperature Operation	50°C 96H Restore 2H at 25°C Power on	
4	Low Temperature Operation	0°C 96H Restore 4H at 25°C Power on	
5	High Temperature/Humidity Operation	50°C±2°C 90%RH 96H Power on	
6	Temperature Cycle	-20°C ————— 60°C 30min 5min 30min after 5 cycle, Restore 2H at 25°C Power off	
7	Vibration Test	10Hz~150Hz, 100m/s ² , 120min	Not allowed cosmetic and electrical defects.
8	Shock Test	Half- sine wave, 300m/s ² , 11ms	

Note: Operation: Supply 2.5V for logic system.

The inspection terms after reliability test, as below

ITEM	Inspection
Contrast	CR>50%
IDD	IDD<200%
Brightness	Brightness>60%
Color Tone	Color Tone+/-0,05

9. Precautions for Use of LCD Modules

9.1 Handling Precautions

9.1.1 The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

9.1.2 If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

9.1.3 Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

9.1.4 The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

9.1.5 If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer.

Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents

9.1.6 Do not attempt to disassemble the LCD Module.

9.1.7 If the logic circuit power is off, do not apply the input signals.

9.1.8 To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

- a. Be sure to ground the body when handling the LCD Modules.
- b. Tools required for assembly, such as soldering irons, must be properly ground.
- c. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

- d. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

9.2 Storage precautions

9.2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

9.2.2 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$

Relatively humidity: $\leq 80\%$

9.2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

9.3 The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.