



PIN DESCRIPTION

Pin	Symbol
1	RX00-
2	RX00+
3	RX01-
4	RX01+
5	RX02-
6	RX02+
7	BIST
8	RXOC-
9	RXOC+
10	RX03-
11	RX03+
12	RXE0-
13	RXE0+
14	GND
15	RXE1-
16	RXE1+
17	GND
18	RXE2-
19	RXE2+
20	RXEC-
21	RXEC+
22	RXE3-
23	RXE3+
24	GND
25	CTL
26	CE
27	NC
28	VDD
29	VDD
30	VDD



Display Type	21.5" TFT, TRANSMISSIVE
	NORMALLY BLACK
Upper Polarization Type	ANTI-GLARE
Viewing Angle	ALL VIEW
LCD Driver IC	TBD
Logic Voltage	VDD=5V
Operation Temperature	0°C TO 50°C
Storage Temperature	-20°C TO 60°C
Interface	LVDS
Backlight	60-LED WHITE
Surface luminance	500cd/m2(TYP.)
White X/Y	

NOTES:  
 1. GENERAL TOLERANCE: ±0.2  
 2. ( ) REFERENCE DIMENSION  
 3. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS

					DRAWN	
					ME.CHECKED	
					EE.CHECKED	
					APPROVED	
V00.		First issue		2023.07.22A	CUSTOMER'S APPROVAL	
VER.	SYMBOL	AMENDMENT	SIGN	DATE		

TITLE				DRAWING NO.			
MODULE SPEC.				VXTL50BJZ-01			
UNIT		mm	SCALE	FIT			
3rd Angle		☉		SHEET 1 OF 1			
Victronix Tecenstar INT'L CO., LTD							